

# EasyView™ Light Meters


**Choice of models for high intensity measurements**  
Up to 400,000 Lux and 40,000 Foot candles

## Features:

- Compact and rugged design features large display
- Multiple wide measuring ranges:  
Model EA30 - 40,000Fc in 4 ranges and 400,000Lux in 5 Ranges  
Model EA31 - 20,000Fc in 4 ranges and 20,000Lux in 4 ranges
- Data hold freezes reading on display
- MIN/MAX readings
- Zero function
- Cosine and color corrected measurements
- Low battery and overrange indication
- Auto power off to save battery life
- Utilizes precision silicon photodiode sensor with 3ft coiled cable for easy storage
- Complete with built-in stand, remote sensor with protective cover, protective rubber holster, and 6 AAA batteries

## Additional features for Model EA30:

- Large display with bargraph
- Peak hold captures short light pulses to 100µSec
- Relative function for zero or difference from reference value



High resolution for low level measurements in places like parking lots, stairwells, and ATM machines

## Ordering Information:

- EA30.....EasyView™ High Intensity Light Meter  
EA30-NIST .....EA30 with NIST Certificate  
EA31.....EasyView™ Light Meter  
EA31-NIST .....EA30 with NIST Certificate

Specifications	Range	Resolution	Basic Accuracy
Light Intensity			
EA30	Lux 40, 400, 4000, 40000, 400000Lux	0.01	±3%rdg + 0.5%FS
	Foot candles 40, 400, 4000, 40000Fc		
EA31	Lux 20, 200, 2000, 20000Lux	0.01	±3%rdg + 0.5%FS
	Foot candles 20, 200, 2000, 20000Fc		
Dimensions	5.9 x 2.8 x 1.4" (150 x 72 x 33mm)		
Weight	8.3oz (235g)		

