

TD-4100XD

HYDROCARBONS IN WATER



Now available with standard E09 Electronics Package and standard EZ Access Flow Cell

The TD-4100 XD is a ruggedized, continuous on-line fluorescence based oil in water monitor. The XD is designed specifically for offshore/onshore oil production, refining, petro-chemical, mining, and other industries that require robust on-line hardware for severe duty and hazardous area locations. The monitor is skid mounted and constructed of 316 stainless steel, including an external keypad, for operation in corrosive environments.

The TD-4100 XD detects and measures crude oil, refined fuels, fuel oils, lubricating or hydraulic fluids, and aromatic solvents in water. Detection limits range from low ppb ($\mu\text{g/L}$) to high ppm (mg/L).



TD-4100XD

HYDROCARBONS IN WATER

Continuous On-Line Monitor

Continuous on-line monitoring with the TD-4100 XD provides the most responsive feedback loop for measuring hydrocarbons in water. Continuous monitoring is reliable, effective, and recognized for its ability to improve process management for treating, discharging and detecting hydrocarbons in water. Compared to laboratory grab sample analysis, on-line monitoring provides cost effective, continuous, remote, operator unattended measurement of hydrocarbons in water.



Non-Contact, Non-Fouling EZ Access Flow Cell

The TD-4100 XD does not have a glass flow cell. Hydrocarbons are detected in a stream of water falling through an open chamber; the water does not contact, dirty or foul the optical windows. A proprietary Air Curtain system keeps optical windows fog-free in hot water applications.

Low Maintenance

The instrument is stable within 10% over 6 months. Other than sample line maintenance, routine maintenance involves changing a lamp twice a year in addition to changing the desiccant plug. System checks are easily performed with the CheckPOINT® solid standard.

Direct, Continuous Monitoring

The TD-4100 XD monitors a flowing water stream continuously. No chemicals, no pre-treatment, no mechanical manipulation or mixing of the sample is required to monitor hydrocarbons in water.

Accurate

The TD-4100 XD directly measures fluorescing hydrocarbons in water with accuracies that consistently correlate to regulatory lab methods in most cases.

High Sensitivity And Selectivity

Sensitive

BTEX, gasoline, diesel, jet fuel, crude oil, aromatic solvents and refined petroleum products are detected by the TD-4100 XD from low ppb ($\mu\text{g/L}$) to high ppm (mg/L). For example, the TD-4100 XD can detect 10 ppb of diesel fuel in water free of interfering compounds.

Selective

The TD-4100 XD continuously measures fluorescent hydrocarbons in water. Fluorescence occurs when a molecule absorbs light energy and emits light energy at longer wavelengths.

Effective Monitoring In Dirty Water

Fluorescence technology makes the TD-4100 XD resistant to interferences from turbid or dirty water that impact on-line UV, IR absorption, or light scatter instruments. Most substances absorb light, but few fluoresce; if a substance does not fluoresce at the specific wavelengths for the monitored hydrocarbon, it will not interfere.

Operator Friendly

The TD-4100 XD with E09 is designed for easy operation. Simple on-board software controls alarms, 4-20 mA output, diagnostics and calibration. "Turner Designs Hydrocarbon Instruments is the recognized expert for oil in water monitoring technology."



TD-4100XD

SPECIFICATIONS



Envelope Dimensions	22" W x 25" D x 95" H [55.5 cm W x 63.5 cm D x 241 cm H]
Weight	180 lbs [82 Kg] plus accessories
Power Requirements	90 - 240 VAC, 50/60 Hz +/- 10%, 184 W, 1 ph, (24 VDC Optional)
Inlet Plumbing Requirements	½" MNPT (standard) or ½" tube
Outlet Plumbing Requirements	1-1/2" MNPT
Inlet Sample Flowrate	2 - 3 US gallons/min [7.5 - 11.5 L/min], optional sample pump
Inlet Sample Pressure	5 - 20 psig [34 - 136 kPag]
Outlet Sample Pressure	Atmospheric (standard) or optional sample return pump
Sample Temperature	-4 to 131 °F [-20 to 55 °C] standard, higher temperatures optional
Ambient Temperature	-4 to 131 °F [-20 to 55 °C] standard, optional cold and high temperature protection
Operational Principle	Fluorescence
Detection Range	1 ppb - 1000 ppm depending upon target hydrocarbon and water quality
Stability	10% or better over 6 months
Response Time	<10 seconds continuous real-time response
Calibration	Multiple-point linear or non-linear, or uncalibrated. Holds two calibrations (one for each sample stream).
Field Validation	Via factory supplied CheckPOINT Solid Check Standard
Alarms	Baseline, early warning, high alarm, system-function, local display and audible tone
Alarm Outputs	Four user-settable, independently-protected dry contact relays
Communication	Standard E09 features with 4-20 mA isolated, 500 ohm impedance, selectable between Loop Powered and Instrument Powered, Ethernet. Optional HART, ModBus
Diagnostics	System failures reports to relay and local display
Security	Two level password protected, lockable cabinet
Electronics Cabinet	316 stainless steel, NEMA 4X, IP 66
Hazardous Area Options	North America: Class I Division 1, Class I Division 2, Groups B, C, D, T4; ATEX and IECEx: Class I Zone 1, Zone 2, other international codes.
Sample Pump	Optional
Cleaning System	Optional
Data Logger	Standard - see E09 Data Sheet
ISO Certified	9001: 2008 Quality System



#1 Worldwide
For Process &
Environmental
Oil In Water Monitors

TURNER DESIGNS
Hydrocarbon Instruments

2023 N. Gateway Blvd., Suite 101
Fresno, California 93727 USA

TEL: 559 253 1414

FAX: 559 253 1090

sales@oilinwatermonitors.com

www.oilinwatermonitors.com

World Wide Sales and Service.

